




X-Series Chargers

Electrical properties

Charging capacity	X7: 7.4kW, 32A, single-phase, Queensland—without Active Device Management: 4.6kW, 20A, single-phase
	X22: 22kW, 32A three-phase
Voltage	230VAC (E7/X7) - 400VAC (X22) 50/60Hz
Cable configuration	(1) External type 2 socket (2) External type 1/2 cable
PSU	Integrated, low standby current (79-265VAC)
Metering	Revenue grade

Connectivity & Features

Cellular modem	LTE-M
WiFi	802.11 b/g/n 2.4 GHz
Ethernet	Yes
Local configuration interface	Bluetooth LE
Display	LED (Network, Charge, Fault)
Control & monitoring	Evnex CP Link Dashboard
Communication protocol	OCPP 1.6J (conditions apply, not available for residential installs)
Authorisation	RFID ISO/IEC 14443, 13.56 Mhz (X-series only)

Safety


Compliance	IEC 61851-1:2017, IEC 61000-6-3:2011, IEC 61000-6-2:2016, CE
DC leakage detection	Yes, internal 6mA RDC-DD
Protection	Over voltage, under voltage, over current, over temperature, ground fault

Physical

Dimensions (mm)	373 (height) x 212 (width) x 142 (depth)
Operating temperature	-25°C to 55°C
Weight	2.3kg (X7-T2S)
IP rating	IP54 indoor/outdoor (white colour is indoor only)
Impact rating	IK08

Model numbers

X7-T2S, X7-T2T, X7-T1T X7-P2S, X7-P2T	X22-T2S, X22-T2T X22-P2S, X22-P2T
--	--------------------------------------



NZ
evnex.com
0800 395 007
sales@evnex.com

AU
evnex.com/au
1800 959 377

evnex